

the other TVBD indicates is available for use to access the database to register its location and receive a list of channels that are available for it to use. Subsequently, the newly registered TVBD must only use the television channels that the database indicates are available for it to use. A fixed device may not obtain lists of available channels from another fixed device as provided by a TV bands database for such other device, *i.e.*, a fixed device may not simply operate on the list of available channels provided by a TV bands database for another fixed device with which it communicates but must contact a database to obtain a list of available channels on which it may operate.

(f) *Security.* (1) For purposes of obtaining a list of available channels and related matters, fixed and Mode II TVBDs shall only be capable of contacting databases operated by FCC designated administrators.

(2) Communications between TV bands devices and TV bands databases are to be transmitted using secure methods that ensure against corruption or unauthorized modification of the data; this requirement applies to communications of channel availability and other spectrum access information between fixed and Mode II devices (it is not necessary for TVBDs to apply security coding to channel availability and channel access information where they are not the originating or terminating device and that they simply pass through).

(3) Communications between a Mode I device and a fixed or Mode II device for purposes of obtaining a list of available channels shall employ secure methods that ensure against corruption or unauthorized modification of the data. When a Mode I device makes a request to a fixed or Mode II device for a list of available channels the receiving device shall check with the TV bands database that the Mode I device has a valid FCC Identifier before providing a list of available channels. Contact verification signals transmitted for Mode I devices are to be encoded with encryption to secure the identity of the transmitting device. Mode I devices using contact verification signals

shall accept as valid for authorization only the signals of the device from which they obtained their list of available channels.

(4) A TV bands database shall be protected from unauthorized data input or alteration of stored data. To provide this protection, the administrator of the TV bands database administrator shall establish communications authentication procedures that allow the fixed or Mode II devices to be assured that the data they receive is from an authorized source.

(5) Applications for certification of TV bands devices are to include a high level operational description of the technologies and measures that are incorporated in the device to comply with the security requirements of this section. In addition, applications for certification of fixed and Mode II devices are to identify at least one of the TV bands databases operated by a designated TV bands database administrator that the device will access for channel availability and affirm that the device will conform to the communications security methods used by that database.

(g) A personal/portable TVBD operating in Mode I may only transmit upon receiving the transmissions of fixed or Mode II TVBD. A personal/portable device operating in Mode I may transmit on either an operating channel of the fixed or Mode II TVBD or on a channel the fixed or Mode II TVBD indicates is available for use.

[74 FR 7326, Feb. 17, 2009, as amended at 75 FR 75837, Dec. 6, 2010; 77 FR 29245, May 17, 2012]

§ 15.712 Interference protection requirements.

(a) Digital television stations, and digital and analog Class A TV, low power TV, TV translator and TV booster stations:

(1) *Protected contour.* TVBDs must protect digital and analog TV services within the contours shown in the following table. These contours are calculated using the methodology in § 73.684 of this chapter and the R-6602 curves contained in § 73.699 of this chapter.

Type of station	Protected contour		
	Channel	Contour (dBu)	Propagation curve
Analog: Class A TV, LPTV, translator and booster	Low VHF (2-6)	47	F(50,50)
	High VHF (7-13)	56	F(50,50)
	UHF (14-69)	64	F(50,50)
Digital: Full service TV, Class A TV, LPTV, translator and booster.	Low VHF (2-6)	28	F(50,90)
	High VHF (7-13)	36	F(50,90)
	UHF (14-51)	41	F(50,90)

(2) *Required separation distance.* TVBDs must be located outside the contours indicated in paragraph (a)(1) of this section of co-channel and adjacent channel stations by at least the minimum distances specified in the following table. Personal/portable TVBDs operating in Mode II must comply with the separation distances specified for an unlicensed device with an antenna height of less than 3 meters. Alternatively, Mode II personal/portable TVBDs may operate at closer separation distances from the contour of adjacent channel stations than this table permits, including inside the contour of adjacent channel stations, provided the power level is reduced to 40 mW or less as specified in § 15.709(a)(2).

Antenna height above average terrain of unlicensed device	Required separation (km) from digital or analog TV (full service or low power) protected contour	
	Co-channel (km)	Adjacent channel (km)
Less than 3 meters	4.0	0.4
3–Less than 10 meters	7.3	0.7
10–Less than 30 meters ...	11.1	1.2
30–Less than 50 meters ...	14.3	1.8
50–Less than 75 meters ...	18.0	2.0
75–Less than 100 meters	21.1	2.1
100–Less than 150 meters	25.3	2.2
150–Less than 200 meters	28.5	2.3
200–250 meters	31.2	2.4

(3) The antenna height above ground for a fixed TVBD may not exceed 30 meters.

(b) *TV translator, Low Power TV (including Class A) and Multi-channel Video Programming Distributor (MVPD) receive sites.* MVPD, TV translator station and low power TV (including Class A) station receive sites located outside the protected contour of the TV station(s) being received may be registered in the TV bands database if they are no farther than 80 km outside the nearest edge of the relevant contour(s). Only

channels received over the air and used by the MVPD, TV translator station or low power/Class A TV station may be registered. TVBDs may not operate within an arc of ± 30 degrees from a line between a registered receive site and the contour of the TV station being received in the direction of the station's transmitter at a distance of up to 80 km from the edge of the protected contour of the received TV station for co-channel operation and up to 20 km from the registered receive site for adjacent channel operation, except that the protection distance shall not exceed the distance from the receive site to the protected contour. Outside of this ± 30 degree arc, TVBDs may not operate within 8 km from the receive site for co-channel operation and 2 km from the receive site for adjacent channel operation. For purposes of this section, a TV station being received may include a full power TV station, TV translator station or low power TV/Class A TV station.

(c) *Fixed Broadcast Auxiliary Service (BAS) Links.* For permanent BAS receive sites appearing in the Commission's Universal Licensing System or temporary BAS receive sites registered in the TV bands database, TVBDs may not operate within an arc of ± 30 degrees from a line between the BAS receive site and its associated permanent transmitter within a distance of 80 km from the receive site for co-channel operation and 20 km for adjacent channel operation. Outside this ± 30 degree arc, TVBDs may not operate within 8 km from the receive site for co-channel operation and 2 km from the receive site for adjacent channel operation.

(d) *PLMRS/CMRS operations:* TVBDs may not operate at distances less than 134 km for co-channel operations and 131 km for adjacent channel operations

§ 15.713

47 CFR Ch. I (10–1–12 Edition)

from the coordinates of the metropolitan areas and on the channels listed in § 90.303(a) of this chapter. For PLMRS/CMRS operations authorized by waiver outside of the metropolitan areas listed in § 90.303(a) of this chapter, co-channel and adjacent channel TVBDs may not operate closer than 54 km and 51 km, respectively from a base station.

(e) *Offshore Radiotelephone Service.* TVBDs may not operate on channels used by the Offshore Radio Service within the geographic areas specified in § 74.709(e) of this chapter.

(f) *Low power auxiliary services, including wireless microphones:* (1) Fixed TVBDs are not permitted to operate within 1 km, and personal/portable TVBDs will not be permitted to operate within 400 meters, of the coordinates of registered low power auxiliary station sites on the registered channels during the designated times they are used by low power auxiliary stations.

(2) TVBDs are not permitted to operate on the first channel on each side of

TV channel 37 (608–614 MHz) that is not occupied by a licensed service.

(g) *Border areas near Canada and Mexico:* Fixed and personal/portable TVBDs shall comply with the required separation distances in § 15.712(a)(2) from the protected contours of TV stations in Canada and Mexico. TVBDs are not required to comply with these separation distances from portions of the protected contours of Canadian or Mexican TV stations that fall within the United States.

(h) *Radio astronomy services:* Operation of fixed and personal/portable TVBDs is prohibited on all channels within 2.4 kilometers at the following locations.

(1) The Naval Radio Research Observatory in Sugar Grove, West Virginia at 38 30 58 N and 79 16 48 W.

(2) The Table Mountain Radio Receiving Zone (TMRZ) at 40 08 02 N and 105 14 40 W.

(3) The following facilities:

Observatory	Latitude (deg/min/sec)	Longitude (deg/min/sec)
Allen Telescope Array	40 49 04 N	121 28 24 W
Arecibo Observatory	18 20 37 N	066 45 11 W
Green Bank Telescope (GBT)	38 25 59 N	079 50 23 W
Very Large Array (VLA)	Rectangle between latitudes 33 58 22 N and 34 14 56 N, and longitudes 107 24 40 W and 107 48 22 W	
Very Long Baseline Array (VLBA) Stations:		
Pie Town, NM	34 18 04 N	108 07 09 W
Kitt Peak, AZ	31 57 23 N	111 36 45 W
Los Alamos, NM	35 46 30 N	106 14 44 W
Ft. Davis, TX	30 38 06 N	103 56 41 W
N. Liberty, IA	41 46 17 N	091 34 27 W
Brewster, WA	48 07 52 N	119 41 00 W
Owens Valley, CA	37 13 54 N	118 16 37 W
St. Croix, VI	17 45 24 N	064 35 01 W
Hancock, NH	42 56 01 N	071 59 12 W
Mauna Kea, HI	19 48 05 N	155 27 20 W

[74 FR 7326, Feb. 17, 2009, as amended at 75 FR 75839, Dec. 6, 2010; 77 FR 29246, May 17, 2012]

§ 15.713 TV bands database.

(a) *Purpose.* The TV bands database serves the following functions:

(1) To determine and provide to a TVBD, upon request, the available TV channels at the TVBD's location. Available channels are determined based on the interference protection requirements in § 15.712. A database must

provide fixed and Mode II personal portable TVBDs with channel availability information that includes scheduled changes in channel availability over the course of the 48 hour period beginning at the time the TVBDs make a re-check contact. In making lists of available channels available to a TVBD, the TV bands database shall ensure that all communications and interactions between the TV bands database and the TVBD include adequate security measures such